Checking and Distributing Statistical Model-Checking

Peter Bulychev
Alexandre David
Kim G. Larsen
Axel Legay
Marius Mikucionis
Danny Bøgsted Poulsen

Outline

- UPPAAL-SMC in a Nutshell
- Distributing SMC
- Checking DSMC
- Case-studies

UPPAAL


A[] forall (i : id_t) forall (j : id_t)
Train(i).Cross && Train(j).Cross imply i == j
Safety
E<> Train(0).Cross and Train(1).Stop
Reachability
Train(0).Appr --> Train(0).Cross
Liveness
A<> .. E[] ..
sup: .. inf: ..
Limited quantitative analysis
Performance properties
State-space explosion
Simulation Trace
Train(3)

UPPAAL SMC


Editor
Simulator
Verifier
Performance properties
Pr[<= 200](<> Train(5).Cross)
Pr[<= 100](<> Train(0).Cross) >= 0.8
Pr[<= 100](<> Train(5).Cross) >=
Pr[<= 100](<> Train(1).Cross)
State-space explosion
Generate random runs
Performance properties
State-space explosion
Train(5)
appr[0]: Train(0) --> Gate
Next
Reset
Simulation Trace
appr[3]: Train(3) --> Gate
stop[tail()]: Gate --> Train(3)
stop[tail()]: Gate --> Train(2)
Open
Save
Random
Slow
Safe
Cross
Appr
Start
Stop
Train(3)
Train(4)
Train(5)

Stochastic Semantics of UPPAAL TA



Stochastic Semantics of UPPAAL TA

Exponential Distribution







Input enabled
broadcast channels

Composition =
Repeated races between components

Queries

Syntax

- Hypothesis testing
  `Pr[<=100](<> expr)>=0.1`
  `x<=100 #<=50 [] expr <=0.5`
- Evaluation
  `Pr[<=100](<> expr)`
- Comparison
  `Pr[<=20](<> e1)>=Pr[<=10](<> e2)`
- Expected value
  `E[<=10;1000](min: expr)`
  Explicit number of runs. Min or max.
- Simulations
  `simulate 10 [<=100]{expr1,expr2}`

Queries
Syntax

- Hypothesis testing
  `Pr[<=100](<> expr)>=0.1`
  `x<=100 #<=50 [] expr <=0.5`
- Evaluation
  `Pr[<=100](<> expr)`
- Comparison
  `Pr[<=20](<> e1)>=Pr[<=10](<> e2)`
- Expected value
  `E[<=10;1000](min: expr)`
  Explicit number of runs. Min or max.
- Simulations
  `simulate 10 [<=100]{expr1,expr2}`

SMC in UPPAAL



- Constant Slope Timed Automata
  - Clocks may have different (integer) slope in different locations.
  - Branching edges with discrete probabilities (weights).
  - Beyond Priced TA, Energy TA. Equal LHA in (non-stochastic) expressive power.
  - Beyond DTMC, beyond CTMC (with multiple rewards)
- All features of UPPAAL supported
  - User defined functions and types
  - Expressions in guards, invariants, clock-rates, delay-rates (rationals), and weights.
- New GUI for plot-composing and exporting.

SMC in UPPAAL

- Constant Slope Timed Automata
  - Clocks may have different (integer) slope in different locations.
  - Branching edges with discrete probabilities (weights).
  - Beyond Priced TA, Energy TA. Equal LHA in (non-stochastic) expressive power
  - Beyond D
- All features
  - User defin
  - Expressior rates (ratio
- New GUI fo



SMC in UPPAAL

- Constant Slope Timed Automata





rates (rationals), and weights.

- New GUI for plot-composing and exporting.

Distributing SMC

- Distributed SMC
  - Evaluation – trivial to parallelize
  - Hypothesis – careful

Hypothesis testing: intuition.



Distributing SMC

- Distributing hypothesis testing.



Distributing SMC – Naïve Approach



Distributing SMC – Naïve Approach



Solving Bias [Younes'05]

Queue the results at a master, use Round-Robin between nodes to accept the results.

Our Implementation

- Use a batch of **B** (e.g 10) runs, transmit one count per batch.
- Use asynchronous communication (MPI)
- Queue results at the master and wait only when the buffer (size=**K**) is full.



Our Implementation

- Senders have a buffer of (**K**) asynchronously sent messages and blocks only when the buffer is full.
- The master periodically add results in the buffer.



Results

16, 32, 128 cores, Vary Buffer & Batch Sizes

"Small" model: Exhibit expected behaviour.













"Big" model: Amortize the differences.

Checking DSMC

- We can model the algorithm inside UPPAAL.
  - Run SMC on it, even DSMC!

```
1 // buffer portion for early termination:
2 const int P = (K<=4)?K : ((K<=8)?5 : ((K<=16)?8 : ((K<=32)?10 : 12)));
3 bool H0 = false, H1 = false; // for hypothesis H0 and H1
4 int batch[N][K]; // buffer of batches (K batches for N nodes)
5 long satisfied =0, unsatisfied =0; // information about filled lines
6 long sat=0, unsat=0, unknown=N*P*B; // early results in unfilled lines
7 long logRatio = 0, ratioLow = 0, ratioUp = 0; // scaled by p.scale
```

Slave Node



Pr[# <= 100](<> Train(5).Cross)





Master Node


!H0 && !H1
req!
i:node_t
deliver[i]?
saveWork(i,value),
value=0
Got
Wait
H0 || H1
Done
time'==0

```
8  void saveWork(const node_t node, const int value) {
9      if (level [node]<=P) { // entered the early results portion
10         sat += value; unsat += B-value; unknown -= B;
11     }
12     batch[node][level [node]] = value; level [node]++; // store
13     if (level [node]==1) { // entered at the lowest level
14         bool filled = forall (i:node_t) level [i]>0;
15         if (filled ) { // line at the lowest level has been filled
16             int L;
17             for (i: node_t) { // shift all queues one by one
18                 satisfied += batch[i][0]; // count as firm results
19                 unsatisfied += B-batch[i][0];
20                 sat -= batch[i][0]; // discount from early results
21                 unsat -= B-batch[i][0]; unknown += B;
22                 level [i]--; // remove from buffer
23                 for (L=0; L<level[i]; ++L) {
24                     batch[i][ L] = batch[i][ L+1]; // shift
25                     if (L==P) { // entered the early results portion
26                         sat += batch[i][L+1]; unsat += B-batch[i][L+1];
27                     }
28                 }
29                 batch[i][ level [i]]=0; // cleanup
30             }
31             logRatio = p.valAcc*satisfied + unsatisfied *p.valRef;
32             if (logRatio <= p.logInf) H0 = true;
33             if (logRatio >= p.logSup) H1 = true;
34         }
35     }
36     ratioLow = p.valAcc*(satisfied +sat+unknown) +
37                p.valRef*(unsatisfied +unsat);
38     ratioUp  = p.valAcc*(satisfied +sat) +
39                p.valRef*(unsatisfied +unsat+unknown);
40     if (ratioUp <= p.logInf) H0 = true;
41     if (ratioLow >= p.logSup) H1 = true;
42 }
```

Read batch.

Exact decision.

Safe approximate decision.

Results

N=16
B=1..10
K=1,2,4,8



Can predict performance.
Can derive more information, e.g., processor usage.
Validate implementation.

Property used:
E[time<=1000; 1000] (max: usage)

Conclusions:
K=1 has huge effect and should be avoided.
K=2 has effect if B<20.
K>2 are indistinguishable on homogeneous cluster.
K>2 and B>20: number of simulations scale linearly to the number of cores used.

Case Studies



FIREWIRE





BLUETOOTH





LMAC

LMAC

Lightweight Media Access Control (LMAC)

- Problem domain:
  - communication scheduling
- Targeted for:
  - self-configuring networks,
  - collision avoidance,
  - low power consumption
- Application domain:
  - wireless sensor networks

LMAC Protocol Design

- Four phases:
  - Initialization (listen until a neighbor is heard)
  - Waiting (delay a random amount of time frames)
  - Discovery (wait for entire frame and note used slots)
  - Active
    - choose free slot,
    - use it to transmit, including info about detected collisions
    - listen on other slots
    - fallback to Discovery if collision is detected
- Only neighbors can detect collision and tell the user-node that its slot is used by others

adopted from A.Fehnker, L.v.Hoesel, A.Mader



Classical vs. Statistical MC

- A.Fehnker, L.v.Hoesel and A.Mader used UPPAAL to explore 4- and 5-node topologies and found cases with perpetual collisions.
- However they could not know whether the next collisions are inevitable.
- Statistical MC offers an insight by calculating the probability over the number of collisions.

  + estimated cost in terms of energy.

LMAC Simple Statistics for 4 Nodes

- Wait distribution:
  - geometric
  - uniform
- Network topology:
  - chain
  - ring
- Collision probability
- Collision count
- Power consumption





Pr[collisions<=50000] (<> time>=1000)

LMAC with Parameterized Topology

Collision probability in a 4 node network of a randomly generated topology:

Pr[time<=200] (<> col_count>0)

	topology	collision probability
(star)		[0.36; 0.39]
		[0.29; 0.36]
		[0.26; 0.30]
		[0.19; 0.21]

	topology	collision probability
		[0.08; 0.19]
(ring)		[0.11; 0.13]
		[0.08; 0.15]
(chain)		[0.049; 0.050]

10-Node Chain







The first collisions can be as late as **800**tu.
It is very likely (**>94%**) that
there will be **0** collisions.
But if they happen, some are perpetual.

10-Node Ring







The first collisions can be as late as **920**tu.
It is very likely (**>90%**) that
there will be **0** collisions.
But if they happen, they are perpetual.

10-Node Star







The first collisions happen before **500**tu.
It is unlikely (**8.2%**) that
there will be **0** collisions.
And if they happen, they are perpetual.

10-Node Random Topologies

Generated **10000** random topologies

Checked the property:

Pr[time<=2000](<> col_count>42)

(perpetual collisions are likely)

One instance on a laptop takes ~**3.5**min

All 10000 instances on 32-core cluster: **409.5**min

There were:

6091 with **>0** probability (shown in histogram)

3909 instances with **0** probability (removed)

The highest probability was **0.63**

While star topology yields **0.91**



Conclusion

- Preliminary experiments indicate that distributed SMC in UPPAAL scales very nicely.

- More work to identify impact of parameters for distributing individual SMC?

- UPPAAL 4.1.9 available
  (support for SMC, DSMC, 64-bit,..)

End